

Shenzhen Enster Electronics Co.,LTD

H.265 5.0 Megapixels Bullet IP Camera 2pcs Array IR leds 40M
IR distance



- 1) H.265 5.0 Megapixels Bullet IP Camera
- 2) Sensor:1/1.8" SONY CMOS sensor with ICR
- 3) Resolution :2592*1944
- 4) Lens: 3.6-10mm(6MP) Adjust for Zoom&Focus
- 5) IR LED: 2pcs Array IR LED IR Range:40m
- 6) Frame Rate:NTSC:30fps PAL:25fps

Option model :

NST-IPH5705 5.0MP

NST-IPH5704 4.0MP

NST-IPH5703 3.0MP

Camera Type		Bullet IP Camera		
System		Embedded RTOS design		
Camera	Effective Pixels	5.0 Mega Pixels	4.0 Megapixels	3.0 Mega Pixels
			Main stream:2592*1944; 3MP;2MP Sub stream:704*576	Main stream:2592*1520; 2048*1536; Sub stream:704*576
Frames Rates		PAL:25fps(2592*1944)	PAL:20fps(2592*1520)/ 25fps(2048*1536)	PAL:25fps(2048*1536)/(*1080)
		NTSC:30fps(2592*1944)	NTSC:20fps(2592*1520)/ 30fps(2048*1536)	NTSC:30fps(2048*1536) 20*1080)
Image Sensor		1/1.8" SONY Exmor IMX178 CMOS Sensor	1/3" OV4689 CMOS Sensor	1/3" Aptina AR0330 CMOS Sensor
		6.29 megapixel resolution (3072H*2048V)	4 Megapixel resolution (2688H*1520V)	3 megapixel resolution (2304H*1536V)
DSP		Dual core 32-bit DSP (Hi3516A)	Dual core 32-bit DSP (Hi3516D)	Dual core 32-bit DSP (Hi3516D)
Min. Illumination	Color	<u>0.001Lux@F1.2</u>	Color 0.01Lux@F1.2	Color 0.01Lux@F1.2

		B/W 0.0001 Lux@F1.2	B/W 0.001 Lux@F1.2	B/W 0.01 Lux@F1.2
	Adjust Parameters	DWDR,BLC,DNR,AE,AGC,D&N,Mirror,Flip,etc.		
Video	Compression	H.265 Main profile	H.265 Main profile	H.265 Main profile
	Stream	support dual stream,AVI format	support dual stream,AVI format	support dual stream,AVI format
	Bit Rate	support 0.1M ~8Mpbs bit rate adjustable	support 0.1M ~8Mpbs bit rate adjustable	support 0.1M ~8Mpbs bit rate adjustable
	Frame Rates	support 1~30fps adjust	support 1~30fps adjust	support 1~30fps adjust
Audio	Input and output	1ch input(micphone),1ch output(Speaker&micphone) Optional		
	Compression	G.711 compression,support two-way audio intercom,support audio and video synchronized output		
Alarm	Types	Motion Detection, Video Blind , Video Loss		
Network	WEB Browser	Support WEB remote config(IE, Safari, Google Chrome, Firefox etc.)		
	Smart Phone	mobile remote Monitoring (iPhone,Android,...)		
	CMS Software	Uniform CMS Software(multiple devices management system)		
	Cloud P2P	www.enster.com ,MYEYE platform and other program,Offer SDK		
	Network	1 * RJ45,10/100M,Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP		
	ONVIF	Support (ONVIF 2.4)		
	POE	Support(optional)		
	WIFI	N/A		
General	Language	20 kinds of languages such as English, Finnish, French, German, Greek,Italian, Japanese, Polish, Portuguese, Russian, Spanish, Thai, S-Chinese, T-Chinese and Turkish		
	IR Cut Filter	Set of double light switch IR-CUT filter		
	Lens Mount	Varifocal Lens 3.6-10 mm(5MP)		
	Infrared Luminary	2pcs Array IR LED		
	Infrared Wavelength	850nm		
	Illuminate Distance	40m		
	Waterproof	IP 66		

Criterion		
I/O Connector	1*DC Connector ,1* RJ45(10/100M Network)	
Supplied Voltage	DC12V/PoE(802.3af/820.3at)	
Power Consumption	IR On: 600mA max., IR Off: Less than 200mA	
Working Environment	-10 ° C~+60 ° C, 10%~90% (Built in Heater being optional added for environment lower than -20 °)	
Weight	1.4kg	